

CONCRETE SEALER

PRODUCT- AND TECHNICAL INFORMATION

 **TRACSOL**

CONCRETE SEALER

- Free of isocyanates
- 145% elongation to break
- 8 minutes open time / processing time
- Permanently flexible
- Mold resistant
- Available in 2 types of packaging



Description

Concrete Sealer is a sealing product specifically developed to repair hairline cracks and minor damages to concrete sleepers (or crossbeams). The unique formulation ensures a long-lasting repair, guaranteeing the preservation of the concrete sleeper. Concrete Sealer should be applied to a clean (also free from green deposits) and dry surface and cures in approximately 8 minutes.

Product information

Article number	314002	314004
Packing	Cartridge 50 ml	uTAH Cartridge 250 ml
Packaging unit	Per Box (25 pieces)	Per Box (12 pieces)

CONCRETE SEALER

Technical Information

Base	Epoxy
Density	1270 kg/m ³
Shore	64 (D)
Open Time	8 Minutes
Drying Time	20 Minutes
Tensile Strength	13 MPa
Elongation at break	145 %
Temperature Resistance	-20°C to +90°C
Application Temperature	+5°C to +35°C

Practical information

Application

Before starting the application with Concrete Sealer, prepare all the necessary materials. Attach the nozzle to the dual cartridge and dispense the first 2 centimeters to achieve the correct mixing ratio. After the application, leave the existing nozzle on the dual cartridge to prevent drying out. Our advice is to use a new nozzle for each new application.

Surface treatment

Provide a clean, dry and grease-free surface. Clean with Tracsol Surface Cleaner.

Cleaning hands

Power & Care Soap

Shelf life

Approximately 18 months if properly sealed and in original packaging in a dry place, between +15°C and +25°C.