

# ***JOINT PRIMER***

*PRODUCT- AND TECHNICAL INFORMATION*

 ***TRACSOL***

# JOINT PRIMER

- **Effective adhesion promoter**
- **Ready to use and easy to apply**
- **Fast drying time (within 8 minutes)**
- **Part of 'Glued Insulated Rail Joints Repair System'**



## Description

Joint Primer is an adhesion promoter. The product is developed to ensure optimum adhesion of the Glued Rail Joints Repair to all types of end post (plastics) and steel of all types of insulated rail joints. Joint Primer dries fast and has an open time of 24 hours.

Joint Primer is also a part of our various Repair Systems. For detailed work instructions see our website.

## Product information

Article number	<b>312001</b>
Packing	<b>Aerosol 500 ml</b>
Packaging unit	<b>Per Box (12 pieces)</b>

# **JOINT PRIMER**

## **Technical Information**

Base	Polymers
Density	740 kg/m <sup>3</sup>
Consistency	Liquid
Temperature Resistance	-20°C to +80°C
Application Temperature	+5°C to +35°C
Open Timer	24 hours
Drying Time	± 8 minutes (20°C)

## **Practical information**

### **Application**

Surface must be clean, dry and free of grease. Clean with the Surface Cleaner. Shake well before use. Spray distance is ± 25cm. Apply directly to the clean ground joint and let this dry. The Joint Primer cures within 8 minutes (with a single layer thickness). Under moist conditions a heatgun can be used to speed up drying time.

### **Surface treatment**

Provide a clean, dry and grease-free surface.

### **Cleaning hands**

Power & Care Soap

### **Shelf life**

Approximately 24 months if properly sealed and in original packaging in a dry place, between +5°C and +25°C. We recommend horizontal storing to ensure that workable substances in these products remain completely liquid.